NSN 5930-01-349-0108

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-0108

Thread Class:

2a single threaded stud

Thread Length:

0.182 inches single threaded stud and 0.192 inches single threaded stud

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Height:

0.732 inches

Body Height:

0.437 inches

Overall Diameter:

Between 0.540 inches and 0.640 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

32 single threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load first voltage and 1.0 amperes inductive load first voltage and 0.5 amperes lamp load first voltage5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

150.00 actuation point degrees fahrenheit and 135.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

NSN 5930-01-349-0108

Thermostatic Switch - Page 2 of 2

Style Designator:

Demilitarization:

No Fiig: A048b0



Disc
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single threaded stud
Specification Data:
81349-mil-s-24236/1 government specification
Shelf Life:
N/a
Unit Of Measure: