NSN 5930-01-349-0110

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-0110

View Online at https://aerobasegroup.com/nsn/5930-01-349-0110
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
Between 1.140 inches and 1.260 inches
Overall Height:
0.500 inches
Body Diameter:
0.640 inches
Body Height:
Between 0.350 inches and 0.405 inches
Unthreaded Mounting Hole Diameter:
Between 0.133 inches and 0.147 inches
Distance Between Mounting Facility Centers:
Between 0.930 inches and 0.944 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
2.0 amperes resistive load first voltage and 1.0 amperes inductive load first voltage and 500.0 milliamperes lamp load first voltage2.0
amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 500.0 milliamperes lamp load second voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
170.00 actuation point degrees fahrenheit and 150.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
115.0 ac at sea level first voltage28.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Madia Far Which Designed

Media For Which Designed:

Gas or liquid

NSN 5930-01-349-0110

Thermostatic Switch - Page 2 of 2



Style Designator:

Disc w/flange

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-24236/24 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A048b0