

View Online at <https://aerobasegroup.com/nsn/5930-01-349-0119>

Thread Class:

2a single mounting facility

Thread Length:

0.156 inches single mounting facility

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

5.030 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Individual Section Quantity:

4

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

02000-4-1

Longest Horizontal Distance Between Mounting Centers:

2.297 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded stud single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level120.0 lowest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Contact Load Current Rating:

2.0 amperes inductive load highest ac voltage rating at sea level 5.0 amperes inductive load lowest ac voltage rating at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0