NSN 5930-01-349-0127

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-0127

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
10.060 inches
Overall Height:
5.000 inches
Overall Width:
4.720 inches
Unthreaded Mounting Hole Diameter:
0.344 inches single mounting facility
Individual Section Quantity:
6
Longest Horizontal Distance Between Mounting Centers:
3.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
7.000 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and legend plate and metallic inclosure
Contact Voltage Rating In Volts:
480.0 ac at sea level250.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
5.0 amperes inductive load ac at sea level2.0 amperes inductive load dc at sea level
Special Features:
Legend plate reads off, pump no.1 stby, pump no. 2 stby, pump no. 3 stby
Style Designator:
Tap, circuit selector
Shelf Life:

N/a

NSN 5930-01-349-0127 Rotary Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A052b0