NSN 5930-01-349-0131

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-0131

Overall Length:

2.453 inches

Overall Height:

Between 3.230 inches and 3.270 inches

Overall Width:

Between 3.230 inches and 3.270 inches

Unthreaded Mounting Hole Diameter:

0.205 inches single mounting facility and 0.225 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.280 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.280 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 each section rear

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Contact Voltage Rating In Volts:

115.0 ac at sea level28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load ac at sea level100.0 milliamperes inductive load dc at sea level and 250.0 milliamperes resistive load dc at

sea level

Special Features:

Legend reads: prim; auto/vl; backup

NSN 5930-01-349-0131

Rotary Switch - Page 2 of 2



| Ctuda | Danian | |
|-------|--------|--------|
| Style | Design | iator: |

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0