# NSN 5930-01-349-0132

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-0132

# Overall Length:

2.453 inches

# **Overall Height:**

Between 3.230 inches and 3.270 inches

## **Overall Width:**

Between 3.230 inches and 3.270 inches

## **Unthreaded Mounting Hole Diameter:**

0.205 inches single mounting facility and 0.225 inches single mounting facility

# Individual Section Quantity:

#### 2

# Longest Horizontal Distance Between Mounting Centers:

2.280 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

2.280 inches single mounting facility

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### Throw Quantity:

3 each section rear

#### Mounting Method:

Unthreaded hole single mounting facility

#### **Features Provided:**

Actuator knob and legend plate

#### **Contact Voltage Rating In Volts:**

115.0 ac at sea level28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

# Terminal Type:

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

#### **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

# **Contact Load Current Rating:**

100.0 milliamperes inductive load ac at sea level and 250.0 milliamperes resistive load ac at sea level75.0 milliamperes resistive load dc at sea level

#### 360 16761

#### **Special Features:**

Legend reads: prim; auto/sl; back-up

# Style Designator:

Tap, circuit selector

# NSN 5930-01-349-0132

Rotary Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

