## NSN 5930-01-349-0133

Rotary Switch Section - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-0133 **Thread Class:** 2a single mounting facility **Thread Length:** 0.688 inches single mounting facility and 0.812 inches single mounting facility **Overall Height:** 1.875 inches **Overall Width:** 1.593 inches **Body Thickness:** 0.250 inches **Distance Between Mounting Facility Centers:** 1.562 inches single mounting facility **Operating Tempurature Range:** -65.0/+100.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Mounting Method:** Strut single mounting facility and threaded stud single mounting facility Thready Qty Per Inch (tpi): 40 single mounting facility **Thread Size:** 0.125 inches single mounting facility **Contact Voltage Rating In Volts:** 110.0 ac at sea level28.0 dc at sea level **Rotor Through Connection Quantity:** 1 single section **Mounting Facility Pattern:** Two position in-line single mounting facility **Terminal Type:** Clip **Contact Switching Action:** Breaks before makes single section frontbreaks before makes single section in-line **Contact Load Current Rating:** 0.5 amperes resistive load ac at sea level2.0 amperes resistive load dc at sea level **Precious Material And Location:** Contact and rotor blade surfaces silver **Precious Material:** Silver **Style Designator:** Switch section, rotary

Thread Series Designator: Unc single mounting facility

## NSN 5930-01-349-0133

Rotary Switch Section - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0