

View Online at <https://aerobasegroup.com/nsn/5930-01-349-1887>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

4.000 inches

**Overall Height:**

6.062 inches

**Overall Width:**

2.344 inches

**Body Height:**

5.218 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Distance Between Mounting Facility Centers:**

2.750 inches

**Capillary Tube Length:**

72.0 inches

**Bulb Length:**

2.594 inches

**Bulb Diameter:**

0.375 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Operating Temperature Rating:**

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Unthreaded hole and bracket

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+30.00/+250.00 actuation point degrees fahrenheit and +30.00/+250.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal actuation point dial and internal deactuation point dial

**Contact Voltage Rating In Volts:**

480.0 ac at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0