

View Online at <https://aerobasegroup.com/nsn/5930-01-349-1887>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

4.000 inches

Overall Height:

6.062 inches

Overall Width:

2.344 inches

Body Height:

5.218 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

2.750 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

2.594 inches

Bulb Diameter:

0.375 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Unthreaded hole and bracket

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+30.00/+250.00 actuation point degrees fahrenheit and +30.00/+250.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point dial and internal deactuation point dial

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0