NSN 5930-01-349-3168

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-3168

Thread Class: 2b single mounting facility **Overall Length:** 8.656 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Individual Section Quantity:** 13 **Longest Horizontal Distance Between Mounting Centers:** 2.297 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level240.0 highest ac voltage rating at sea level125.0 lowest ac voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 16 single actuator **Terminal Type:** Tab w/screw **Switch Actuator Positioning Increment:** 22.5 degrees single actuator **Contact Load Current Rating:** 5.0 amperes resistive load dc at sea level2.0 amperes resistive load highest ac voltage rating at sea level5.0 amperes resistive load lowest ac voltage rating at sea level **Precious Material And Location:** Contact surfaces silver

Silver

Style Designator:

Precious Material:

Tap, circuit selector

NSN 5930-01-349-3168 Rotary Switch - Page 2 of 2



Thread	Series	Design	ator

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0