## NSN 5930-01-349-3169

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-3169

**Thread Class:** 

2b single mounting facility

**Thread Length:** 

0.365 inches single mounting facility and 0.385 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Corrosion resistant

**Overall Length:** 

**3.232** inches

**Overall Height:** 

1.468 inches

**Overall Width:** 

1.312 inches

**Shaft Diameter:** 

2.250 inches single actuator

**Shaft Length:** 

1.875 inches single actuator

**Nonturn Device Radius:** 

0.437 inches at 3: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

6 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Clip

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

60.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

## NSN 5930-01-349-3169

Rotary Switch - Page 2 of 2



## **Contact Load Current Rating:**

0.5 amperes resistive load ac at sea level 1.5 amperes resistive load dc at sea level

## **Precious Material And Location:**

Contact and terminal surfaces silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0