NSN 5930-01-349-3174

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-3174

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Driptight and dustproof

Body Width:

0.750 inches

Body Height:

0.750 inches

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.160 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.210 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes

inductive dc and 2.500 amperes lamp dc

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5930-01-349-3174

Push Switch - Page 2 of 2

Fiig: A053a0

