

View Online at <https://aerobasegroup.com/nsn/5930-01-349-5465>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

2.720 inches

**Overall Height:**

0.800 inches

**Overall Width:**

0.800 inches

**Body Width:**

0.781 inches

**Body Height:**

0.781 inches

**Actuator Length:**

0.684 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.070 inches

**Actuator Width:**

0.684 inches

**Actuator Color:**

White single actuator and white single actuator

**Illuminated Actuator Color:**

White single actuator and white single actuator

**Actuator Inscription:**

S1 on/xmtr on single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**End Application:**

4935-00-177-9502 supplementary equipment, guided missile system test station

**Mounting Surface To Terminal End Distance:**

2.650 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Horizontal split lens

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 0.750 amperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 0.750 amperes lamp ac

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0