# NSN 5930-01-349-5682

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-5682

# **Thread Class:**

2b single pressure connection

## **Inside Diameter:**

0.438 inches single connection

# **Overall Length:**

5.750 inches

#### **Overall Height:**

11.156 inches

#### **Overall Width:**

2.880 inches

**Body Length:** 

#### 4.880 inches

**Body Height:** 

#### 11.000 inches

## **Unthreaded Mounting Hole Diameter:**

0.375 inches

# Longest Horizontal Distance Between Mounting Centers:

4.250 inches

# Longest Vertical Distance Between Mounting Centers:

3.000 inches

# Shortest Vertical Distance Between Mounting Centers:

1.938 inches

# End Application:

Rowpu, 3k gph

# Pressure Switch Type:

Gage

# **Mounting Method:**

Bracket and unthreaded hole

#### **Features Provided:**

Electrical access port

#### **Contact Action Stimulus:**

Increase

#### **Thread Size:**

0.438 inches single pressure connection

#### **Mounting Facility Pattern:**

Isosceles triangle

# Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary

# Criticality Code Justification:

Feat

#### **Terminal Type:**

Screw

# **NSN 5930-01-349-5682** Pressure Switch - Page 2 of 2



Contact Load Current Rating:
16.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point adjustable, preset
Contact Adjustment Range:
+250.00/+3000.00 actuation point pounds per square inch gage
Contact Adjustment Type:
Internal actuation point screw with scale
Contact Stimulus Rating:
950.00 actuation point pounds per square inch gage
Contact Voltage Rating In Volts:
115.0 ac at sea level single voltage
Pressure Connector Type:
Plain, threaded internal single connection
Special Features:
Weapon system essential
Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A048b0