## NSN 5930-01-349-5688

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-349-5666
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Driptight and dustproof
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.160 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.210 inches
nclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes
nductive dc and 2.500 amperes lamp dc
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Domilitarization

No

## NSN 5930-01-349-5688

Push Switch - Page 2 of 2



Fiig:

A053a0