# NSN 5930-01-349-8972

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-349-8972

**Thread Class:** 

2a 2nd mounting facility

Thread Length:

0.312 inches 2nd mounting facility

**Overall Length:** 

1.416 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.375 inches single actuator

**Overall Diameter:** 

0.687 inches

1

**Individual Section Quantity:** 

**Operating Tempurature Range:** 

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

7 single section rear

**Mounting Method:** 

Printed circuit 1st mounting facilitythreaded bushing 2nd mounting facility

**Thread Size:** 

0.250 inches 2nd mounting facility

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 single section

**Switch Actuator Indexing Position Quantity:** 

7 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Printed circuit

**Contact Switching Action:** 

Breaks before makes single section rear

# NSN 5930-01-349-8972

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

# **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level250.0 milliamperes inductive load dc at sea level and 500.0 milliamperes resistive load dc at sea level

# **Style Designator:**

Tap, circular, bushing mount

### **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unef 2nd mounting facility

### **Specification Data:**

81349-mil-s-3786/39 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0