

View Online at <https://aerobasegroup.com/nsn/5930-01-349-9845>

Thread Length:

0.500 inches single bolt

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.000 inches

Overall Height:

3.500 inches

Overall Width:

2.500 inches

Body Length:

2.500 inches

Body Height:

2.360 inches

Longest Horizontal Distance Between Mounting Centers:

1.780 inches

Shortest Horizontal Distance Between Mounting Centers:

0.890 inches

Longest Vertical Distance Between Mounting Centers:

1.900 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bolt

Contact Action Stimulus:

Increase

Proof Pressure:

3000.00 pounds per square inch

Thread Size:

0.500 inches single bolt

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

15.0 amperes resistive load first voltage15.0 amperes resistive load second voltage15.0 amperes resistive load third voltage4.0 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+5.00/+80.00 actuation point pounds per square inch and +2.00/+68.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point shaft with scale and external deactuation point shaft with scale

Contact Voltage Rating In Volts:

125.0 ac at sea level first voltage 250.0 ac at sea level second voltage 480.0 ac at sea level third voltage 125.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single bolt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0