

View Online at <https://aerobasegroup.com/nsn/5930-01-349-9845>

**Thread Length:**

0.500 inches single bolt

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.000 inches

**Overall Height:**

3.500 inches

**Overall Width:**

2.500 inches

**Body Length:**

2.500 inches

**Body Height:**

2.360 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.780 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.890 inches

**Longest Vertical Distance Between Mounting Centers:**

1.900 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Bolt

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

3000.00 pounds per square inch

**Thread Size:**

0.500 inches single bolt

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

15.0 amperes resistive load first voltage15.0 amperes resistive load second voltage15.0 amperes resistive load third voltage4.0 amperes resistive load fourth voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+5.00/+80.00 actuation point pounds per square inch and +2.00/+68.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point shaft with scale and external deactuation point shaft with scale

**Contact Voltage Rating In Volts:**

125.0 ac at sea level first voltage 250.0 ac at sea level second voltage 480.0 ac at sea level third voltage 125.0 dc at sea level fourth voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single bolt

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0