

View Online at <https://aerobasegroup.com/nsn/5930-01-350-1221>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Vibration resistant and shock resistant and salt spray resistant and moisture resistant and explosion proof

Overall Length:

3.060 inches

Overall Height:

0.740 inches

Overall Width:

0.740 inches

Body Width:

0.740 inches

Body Height:

0.740 inches

Case Material:

Metal

Actuator Length:

0.740 inches

Actuator Style:

Rectangular

Actuator Width:

0.740 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Red single actuator and amber single actuator and blue single actuator and green single actuator

Actuator Inscription:

Man/full/alt single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Mounting Surface To Terminal End Distance:

3.060 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Four-way split lens

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

Extra Long Reference Number:

800a1c1e2j3l2n1 (www) 100 man/full/alt

Precious Material And Location:

Contacts silver and contact surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

12 tab, solder lug

Reference Number Differentiating Characteristics:

As differentiated by extra long reference number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0