NSN 5930-01-350-4115

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Thread Class:

Body Style: Panel mount

Shock resistant

Overall Length:

2a



View Online at https://aerobasegroup.com/nsn/5930-01-350-4115

1.813 inches	
Overall Height:	
4.375 inches	
Overall Width:	
1.515 inches	
Body Length:	
1.813 inches	
Body Width:	
1.515 inches	
Body Height:	
3.875 inches	
Actuator Length:	
1.250 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.125 inches	
Actuator Width:	
0.469 inches	
Actuator Color:	
White single actuator	
Illuminated Actuator Color:	
White single actuator	
Actuator Inscription:	
Elevator interlock release single actuator	
Maximum Voltage Rating In Volts:	
28.0 dc and 115.0 ac	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel and threaded stud	
Features Provided:	
Full display lens	
Thready Qty Per Inch (tpi):	
32	

NSN 5930-01-350-4115

Push Switch - Page 2 of 2

A053a0



Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac
Special Features:
Actuator inscription is amber
Thread Series Designator:
Unc
Terminal Type And Quantity:
12 turret and 4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: