

View Online at <https://aerobasegroup.com/nsn/5930-01-350-4115>

**Thread Class:**

2a

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Shock resistant

**Overall Length:**

1.813 inches

**Overall Height:**

4.375 inches

**Overall Width:**

1.515 inches

**Body Length:**

1.813 inches

**Body Width:**

1.515 inches

**Body Height:**

3.875 inches

**Actuator Length:**

1.250 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.125 inches

**Actuator Width:**

0.469 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Elevator interlock release single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel and threaded stud

**Features Provided:**

Full display lens

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Special Features:**

Actuator inscription is amber

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

12 turret and 4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0