# NSN 5930-01-350-5701

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-350-5701

#### **Body Style:**

Panel mounted

## Hazardous Locations/environmental Protection:

Shock resistant

## **Overall Length:**

3.430 inches

## **Overall Height:**

1.250 inches

#### **Overall Width:**

0.990 inches

#### **Body Length:**

3.160 inches

## **Body Width:**

0.990 inches

#### \_ . .. . .

Body Height:

## 1.250 inches

Case Material:

#### Metal

Actuator Length:

1.000 inches

#### **Actuator Style:**

Rectangular

#### Actuator Height:

0.270 inches

## Actuator Width:

0.750 inches

#### Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

Green single actuator

#### **Actuator Inscription:**

Seq on single actuator

### Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

#### **Features Provided:**

Full display lens and lamp holder and actuator seal

## Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit



## NSN 5930-01-350-5701

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

#### **Precious Material And Location:**

Contacts silver and contact surfaces gold

## Unable To Decode:

Unable to decode and unable to decode

## Terminal Type And Quantity:

1 socket, integrated wire termination

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A053a0