NSN 5930-01-350-5712

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted

Shock resistant

Overall Length:
3.430 inches

Overall Height:
1.250 inches



View Online at https://aerobasegroup.com/nsn/5930-01-350-5712

(Overall Width:
(0.990 inches
E	Body Length:
3	3.160 inches
E	Body Width:
(0.990 inches
E	Body Height:
1	1.250 inches
(Case Material:
ľ	Metal
1	Actuator Length:
1	1.000 inches
,	Actuator Style:
F	Rectangular
1	Actuator Height:
(0.270 inches
,	Actuator Width:
(0.750 inches
1	Actuator Color:
١	White single actuator
I	Iluminated Actuator Color:
١	White single actuator
,	Actuator Inscription:
	Occ well dk single actuator
ľ	Maximum Voltage Rating In Volts:
2	28.0 dc and 115.0 ac
I	nclosure Type:
F	Fully enclosed
ľ	Mounting Method:
F	Panel
F	Features Provided:
F	Full display lens and lamp holder and actuator seal
1	Nonpile-up Contact Arrangement:
4	4 pole, double throw, both positions maintained single switch unit

NSN 5930-01-350-5712

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

Precious Material And Location:

Contacts silver and contact surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0