NSN 5930-01-350-6600

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted

Shock resistant



View Online at https://aerobasegroup.com/nsn/5930-01-350-6600

3.430 inches Overall Height: 0.990 inches Overall Width: 1.250 inches Body Length: 3.160 inches Body Width: 1.250 inches Body Width: 1.250 inches Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 de and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement: 3 pole, double throw, one position momentary single switch unit	Overall Length:
O.yearl Width: 1.250 inches Body Length: 3.160 inches Body Width: 1.250 inches Body Width: 1.250 inches Body Height: 0.990 inches Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 28.0 de and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	3.430 inches
Overall Width: 1.250 inches Body Length: 3.160 inches Body Width: 1.250 inches Body Width: 1.250 inches Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Width: 0.750 inches Actuator Color: White single actuator White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Overall Height:
1.250 inches Body Length: 3.160 inches Body Width: 1.250 inches Body Width: 1.250 inches Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 de and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator Seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	0.990 inches
Body Length: 3.160 inches Body Width: 1.250 inches Body Height: 0.990 inches Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 de and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Overall Width:
3.160 inches Body Width: 1.250 inches Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	1.250 inches
Body Width: 1.250 inches Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 de and 115.0 ae Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Body Length:
1.250 inches Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	3.160 inches
Body Height: 0.990 inches Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Body Width:
Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	1.250 inches
Case Material: Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Body Height:
Metal Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	0.990 inches
Actuator Length: 1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Case Material:
1.000 inches Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Metal
Actuator Style: Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Actuator Length:
Rectangular Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	1.000 inches
Actuator Height: 0.270 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Actuator Style:
O.270 inches Actuator Width: O.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Rectangular
Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Actuator Height:
O.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	0.270 inches
Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Actuator Width:
White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	0.750 inches
Illuminated Actuator Color: White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Actuator Color:
White single actuator Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	White single actuator
Actuator Inscription: Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Illuminated Actuator Color:
Ack single actuator Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	White single actuator
Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Actuator Inscription:
28.0 dc and 115.0 ac Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Ack single actuator
Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Maximum Voltage Rating In Volts:
Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	28.0 dc and 115.0 ac
Mounting Method: Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Inclosure Type:
Panel Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Fully enclosed
Features Provided: Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Mounting Method:
Actuator seal and full display lens and lamp holder Nonpile-up Contact Arrangement:	Panel
Nonpile-up Contact Arrangement:	Features Provided:
	Actuator seal and full display lens and lamp holder
3 pole, double throw, one position momentary single switch unit	Nonpile-up Contact Arrangement:
, i	3 pole, double throw, one position momentary single switch unit

NSN 5930-01-350-6600

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0