NSN 5930-01-350-6611

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted

Shock resistant

Overall Length:
3.430 inches

Overall Height:
1.250 inches



View Online at https://aerobasegroup.com/nsn/5930-01-350-6611

Overall Width:	
0.990 inches	
Body Length:	
3.160 inches	
Body Width:	
0.990 inches	
Body Height:	
1.250 inches	
Case Material:	
Metal	
Actuator Length:	
1.000 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.270 inches	
Actuator Width:	
0.750 inches	
Actuator Color:	
White single actuator	
Illuminated Actuator Color:	
Red single actuator	
Actuator Inscription:	
Gp16 off single actuator	
Maximum Voltage Rating In Volts:	
28.0 dc and 115.0 ac	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel	
Features Provided:	
Full display lens and lamp holder and actuator seal	
Nonpile-up Contact Arrangement:	
2 pole, double throw, one position momentary single switch unit	

NSN 5930-01-350-6611

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

Precious Material And Location:

Contacts silver and contact surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0