## NSN 5930-01-350-6616

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

**Body Style:**Panel mounted

Shock resistant

Overall Length:
3.430 inches

Overall Height:
1.250 inches



View Online at https://aerobasegroup.com/nsn/5930-01-350-6616

0	overall Width:
0	.990 inches
В	ody Length:
3	.160 inches
В	ody Width:
0	.990 inches
В	ody Height:
1	.250 inches
С	case Material:
N	1etal
Α	ctuator Length:
1	.000 inches
Α	ctuator Style:
R	ectangular
Α	ctuator Height:
0	.270 inches
Α	ctuator Width:
0	.750 inches
Α	ctuator Color:
٧	/hite single actuator
II	luminated Actuator Color:
G	Green single actuator
Α	ctuator Inscription:
G	Sp20 on single actuator
N	laximum Voltage Rating In Volts:
2	8.0 dc and 115.0 ac
Ir	nclosure Type:
F	ully enclosed
V	lounting Method:
Ρ	anel
F	eatures Provided:
F	ull display lens and lamp holder and actuator seal
Ν	lonpile-up Contact Arrangement:
2	pole, double throw, one position momentary single switch unit

## NSN 5930-01-350-6616

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

## **Precious Material And Location:**

Contacts silver and contact surfaces gold

**Unable To Decode:** 

Unable to decode and unable to decode

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0