# NSN 5930-01-350-7409

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-350-7409

# **Body Style:**

Panel mounted

# Hazardous Locations/environmental Protection:

Shock resistant

# **Overall Length:**

3.430 inches

#### **Overall Height:**

0.990 inches

#### **Overall Width:**

1.250 inches

#### **Body Length:**

3.160 inches

# Body Width:

1.250 inches

#### \_\_\_\_\_

Body Height:

# 0.990 inches

Case Material:

Metal

## Actuator Length:

1.000 inches

#### Actuator Style:

Rectangular

#### Actuator Height:

0.270 inches

# Actuator Width:

0.750 inches

#### Actuator Color:

White single actuator

#### Illuminated Actuator Color:

Green single actuator

#### **Actuator Inscription:**

Gp15 on single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

#### Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

#### **Features Provided:**

Actuator seal and full display lens and lamp holder

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

# NSN 5930-01-350-7409

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

#### **Precious Material And Location:**

Contact surfaces gold and contacts silver

# Unable To Decode:

Unable to decode and unable to decode

# Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0