## NSN 5930-01-350-8312

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

**Body Style:**Panel mounted

Shock resistant

Overall Length:
3.430 inches

Overall Height:
1.250 inches



View Online at https://aerobasegroup.com/nsn/5930-01-350-8312

| Overall Width:  |
|---|
| 0.990 inches  |
| Body Length:  |
| 3.160 inches  |
| Body Width:   |
| 0.990 inches  |
| Body Height:  |
| 1.250 inches  |
| Case Material:  |
| Metal   |
| Actuator Length:  |
| 1.000 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.270 inches  |
| Actuator Width:   |
| 0.750 inches  |
| Actuator Color:   |
| White single actuator   |
| Illuminated Actuator Color:                                     |
| Green single actuator   |
| Actuator Inscription:   |
| Seq off single actuator   |
| Maximum Voltage Rating In Volts:                                |
| 28.0 dc and 115.0 ac  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Features Provided:  |
| Full display lens and lamp holder and actuator seal             |
| Nonpile-up Contact Arrangement:                                 |
| 2 pole, double throw, one position momentary single switch unit |

## NSN 5930-01-350-8312

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

## **Precious Material And Location:**

Contacts silver and contact surfaces gold

**Unable To Decode:** 

Unable to decode and unable to decode

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0