NSN 5930-01-350-8314

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-350-8314

| Body Style: |
|---|
| Panel mounted |
| Overall Length: |
| 3.430 inches |
| Overall Height: |
| 0.990 inches |
| Overall Width: |
| 1.250 inches |
| Body Length: |
| 3.160 inches |
| Body Width: |
| 1.250 inches |
| Body Height: |
| 0.990 inches |
| Actuator Length: |
| 1.000 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.270 inches |
| Actuator Width: |
| 0.750 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Green single actuator |
| Actuator Inscription: |
| Zone/4 on single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Actuator seal and full display lens |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive ac and 3.500 amperes inductive ac and 7.500 amperes resistive dc and 5.000 amperes inductive dc |

Precious Material And Location:

Contacts silver and contact surfaces gold

NSN 5930-01-350-8314

Push Switch - Page 2 of 2



| | | | _ | _ | | | |
|--------|---|---|----|-----|---|--------|----|
| na | h | _ | Го | 116 | ~ | \sim | ο. |
| | | | | | | | |

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0