NSN 5930-01-350-8316

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-350-8316

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

3.430 inches

Overall Height:

0.990 inches

Overall Width:

1.250 inches

Body Length:

3.160 inches

Body Width:

1.250 inches

Body Height:

0.990 inches

Case Material:

Metal

Actuator Length:

1.000 inches

Actuator Style:

Rectangular

Actuator Height:

0.270 inches

Actuator Width:

0.750 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Green single actuator

Actuator Inscription:

Gp1 on single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and full display lens and lamp holder

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit



NSN 5930-01-350-8316

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0