NSN 5930-01-350-8318

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted

Shock resistant

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-350-8318

2 pole, double throw, one position momentary single switch unit	
Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit	
Actuator seal and full display lens and lamp holder	
Features Provided:	
Panel	
Mounting Method:	
Fully enclosed	
Inclosure Type:	
28.0 dc and 115.0 ac	
Maximum Voltage Rating In Volts:	
Gp2 off single actuator	
Actuator Inscription:	
Red single actuator	
Illuminated Actuator Color:	
White single actuator	
Actuator Color:	
0.750 inches	
Actuator Width:	
0.270 inches	
Actuator Height:	
Rectangular	
Actuator Style:	
1.000 inches	
Actuator Length:	
Metal	
Case Material:	
0.990 inches	
Body Height:	
1.250 inches	
Body Width:	
3.160 inches	
Body Length:	
1.250 inches	
Overall Width:	
0.990 inches	
Overall Height:	
3.430 inches	

NSN 5930-01-350-8318

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0