

View Online at <https://aerobasegroup.com/nsn/5930-01-350-8684>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Shock proof and watertight

**Overall Length:**

6.615 inches

**Overall Height:**

2.780 inches

**Overall Width:**

1.650 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Actuator Length:**

2.500 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

1.000 inches

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.320 inches

**Housing Height:**

1.780 inches

**Housing Length:**

2.840 inches

**Housing Width:**

1.650 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.340 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.160 inches

**Maximum Voltage Rating In Volts:**

230.0 dc and 440.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole and unthreaded hole

**Features Provided:**

Electrical access port

**Thread Size:**

0.190 inches

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

50.0 milliamperes resistive dc and 750.0 milliamperes resistive ac

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0