NSN 5930-01-350-8695

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted

Shock resistant

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-350-8695

3.430 inch	nes
Overall H	leight:
0.990 inch	hes
Overall W	Vidth:
1.250 inch	hes
Body Len	ngth:
3.160 inch	hes
Body Wic	dth:
1.250 inch	hes
Body Hei	ight:
0.990 inch	hes
Case Mat	terial:
Metal	
Actuator	Length:
1.000 inch	hes
Actuator	Style:
Rectangu	ılar
Actuator	Height:
0.270 inch	hes
Actuator	Width:
0.750 inch	hes
Actuator	Color:
White sing	gle actuator
Illuminate	ed Actuator Color:
Green sin	ngle actuator
Actuator	Inscription:
Gp9 on si	ingle actuator
Maximum	n Voltage Rating In Volts:
28.0 dc ar	nd 115.0 ac
Inclosure	е Туре:
Fully encl	osed
Mounting	g Method:
Panel	
Features	Provided:
Actuator s	seal and full display lens and lamp holder
Nonpile-u	up Contact Arrangement:
2 pole do	ouble throw, one position momentary single switch unit

NSN 5930-01-350-8695

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0