## NSN 5930-01-350-8707

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-350-8707

| Body Style:   |
|---|
| Panel mounted   |
|   |
| Overall Length:   |
| 3.430 inches  |
| Overall Height:   |
| 0.990 inches  |
| Overall Width:  |
| 1.250 inches  |
| Body Length:  |
| 3.160 inches  |
| Body Width:   |
| 1.250 inches  |
| Body Height:  |
| 0.990 inches  |
| Actuator Length:  |
| 1.000 inches  |
| Actuator Style:   |
| Rectangular Assurator United to   |
| Actuator Height:  |
| 0.270 inches  |
| Actuator Width:   |
| 0.750 inches  |
| Actuator Color:   |
| White single actuator  Illuminated Actuator Color:  |
|   |
| Red single actuator  Actuator Inscription   |
| Actuator Inscription:   |
| Gp29/off single actuator  Maximum Voltage Pating In Voltage   |
| Maximum Voltage Rating In Volts:  |
| 115.0 ac and 28.0 dc Inclosure Type:  |
| •   |
| Fully enclosed  Mayorting Mathada   |
| Mounting Method: Panel  |
| Features Provided:  |
| Actuator seal and full display lens   |
| Nonpile-up Contact Arrangement:   |
| 2 pole, double throw, one position momentary single switch unit   |
| Contact Load Current Rating At Maximum Rated Voltage:   |
| 5 000 amperes resistive ac and 3 500 amperes inductive ac and 7 500 amperes resistive do and 5 000 amperes inductive do |

Contacts silver and contact surfaces gold

**Precious Material And Location:** 

## NSN 5930-01-350-8707

Push Switch - Page 2 of 2



|   |   |   |   |   | _  | _ |   |   |                     |   |   |  |
|---|---|---|---|---|----|---|---|---|---------------------|---|---|--|
| ı | n | 2 | h | 0 | To |   | 0 | ^ | $\boldsymbol{\sim}$ | ~ | Δ |  |
|   |   |   |   |   |    |   |   |   |                     |   |   |  |

Unable to decode and unable to decode

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0