

View Online at <https://aerobasegroup.com/nsn/5930-01-350-9491>

**Overall Length:**

3.970 inches

**Overall Height:**

6.970 inches

**Overall Width:**

1.640 inches

**Body Height:**

3.970 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Line

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

10000.00 pounds per square inch

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes resistive load first voltage and 10.0 amperes inductive load first voltage10.0 amperes resistive load second voltage and 10.0 amperes inductive load second voltage10.0 amperes resistive load third voltage and 10.0 amperes inductive load third voltage10.0 amperes resistive load fourth voltage and 10.0 amperes inductive load fourth voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+550.00/+5000.00 actuation point pounds per square inch and +350.00/+4400.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level first voltage120.0 ac at sea level second voltage600.0 dc at sea level third voltage115.0 dc at sea level fourth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 first voltage60.0 second voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0