

View Online at <https://aerobasegroup.com/nsn/5930-01-350-9491>

Overall Length:

3.970 inches

Overall Height:

6.970 inches

Overall Width:

1.640 inches

Body Height:

3.970 inches

Pressure Switch Type:

Differential

Mounting Method:

Line

Contact Action Stimulus:

Increase

Proof Pressure:

10000.00 pounds per square inch

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load first voltage and 10.0 amperes inductive load first voltage10.0 amperes resistive load second voltage and 10.0 amperes inductive load second voltage10.0 amperes resistive load third voltage and 10.0 amperes inductive load third voltage10.0 amperes resistive load fourth voltage and 10.0 amperes inductive load fourth voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+550.00/+5000.00 actuation point pounds per square inch and +350.00/+4400.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage120.0 ac at sea level second voltage600.0 dc at sea level third voltage115.0 dc at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage60.0 second voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0