NSN 5930-01-350-9491

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-350-9491

Overall Length:
3.970 inches
Overall Height:
6.970 inches
Overall Width:
1.640 inches
Body Height:
3.970 inches
Pressure Switch Type:
Differential
Mounting Method:
Line
Contact Action Stimulus:
Increase
Proof Pressure:
10000.00 pounds per square inch
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
10.0 amperes resistive load first voltage and 10.0 amperes inductive load first voltage10.0 amperes resistive load second voltage and 10.0
amperes inductive load second voltage10.0 amperes resistive load third voltage and 10.0 amperes inductive load third voltage10.0 amperes
resistive load fourth voltage and 10.0 amperes inductive load fourth voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+550.00/+5000.00 actuation point pounds per square inch and +350.00/+4400.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal actuation point screw and internal deactuation point screw
Contact Voltage Rating In Volts:
600.0 ac at sea level first voltage120.0 ac at sea level second voltage600.0 dc at sea level third voltage115.0 dc at sea level fourth voltage
Pressure Connector Type:
Plain, threaded internal single connection
Frequency In Hertz:
60.0 first voltage60.0 second voltage
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5930-01-350-9491

Pressure Switch - Page 2 of 2



em			

No

Fiig:

A048b0