

View Online at <https://aerobasegroup.com/nsn/5930-01-350-9500>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

1.320 inches

Overall Width:

0.890 inches

Bushing Length:

0.468 inches

Body Length:

1.320 inches

Body Width:

0.890 inches

Body Height:

1.470 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

End Application:

2320-01-304-2277 truck, palletized loading

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

18.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 11.000 amperes resistive ac and 8.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0