

View Online at <https://aerobasegroup.com/nsn/5930-01-350-9500>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

1.320 inches

**Overall Width:**

0.890 inches

**Bushing Length:**

0.468 inches

**Body Length:**

1.320 inches

**Body Width:**

0.890 inches

**Body Height:**

1.470 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Height:**

0.690 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**End Application:**

2320-01-304-2277 truck, palletized loading

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

18.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 11.000 amperes resistive ac and 8.000 amperes inductive ac and 2.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0