NSN 5930-01-350-9502

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-350-9502

Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.495 inches and 0.505 inches
Overall Height:
0.499 inches
Overall Width:
0.437 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.437 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.125 inches
Actuator Style:
Rectangular
Actuator Height:
0.062 inches
Actuator Width:
0.125 inches
Actuator Free Position Height:
Between 0.396 inches and 0.416 inches
Maximum Voltage Rating In Volts:
1.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
8.0 ounces
Actuator Movement:
0.050 pretravel inches
Contact Load Current Rating At Maximum Rated Voltage:
0.5 milliamperes resistive dc

NSN 5930-01-350-9502 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A053a0