## NSN 5930-01-350-9507

Push Switch - Page 1 of 2

**Body Style:**Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-01-350-9507

Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
3.430 inches
Overall Height:
0.990 inches
Overall Width:
1.250 inches
Body Length:
3.160 inches
Body Width:
1.250 inches
Body Height:
0.990 inches
Case Material:
Metal
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.750 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Gp7 on single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and full display lens and lamp holder
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-350-9507

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

## **Precious Material And Location:**

Contact surfaces gold and contacts silver

**Unable To Decode:** 

Unable to decode and unable to decode

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0