

View Online at <https://aerobasegroup.com/nsn/5930-01-350-9512>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Driptight and shock resistant

Overall Length:

1.375 inches

Overall Width:

0.562 inches

Bushing Length:

Between 0.359 inches and 0.391 inches

Body Length:

0.876 inches

Body Width:

0.562 inches

Case Material:

Metal

Actuator Style:

Round, flush

Actuator Diameter:

Between 0.733 inches and 0.745 inches

Actuator Height:

0.250 inches

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action, with contact on arm single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-st-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UN2f

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

96906-ms25089 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-s-8805 spec.