

View Online at <https://aerobasegroup.com/nsn/5930-01-351-0509>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

1.266 inches

**Overall Height:**

0.688 inches

**Body Diameter:**

0.750 inches

**Mounting Slot Width:**

0.140 inches

**Body Height:**

0.626 inches

**Distance Between Mounting Facility Centers:**

1.000 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between 0.0 degrees celsius and 65.0 degrees celsius

**Mounting Method:**

Bracket and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.5 amperes resistive load first voltage 1.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+122.00/+221.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Stimulus Rating:**

149.00 actuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage 28.0 dc at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0