

View Online at <https://aerobasegroup.com/nsn/5930-01-351-0510>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

1.266 inches

Overall Height:

0.688 inches

Body Diameter:

0.750 inches

Mounting Slot Width:

0.140 inches

Body Height:

0.626 inches

Distance Between Mounting Facility Centers:

1.000 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between 0.0 degrees celsius and 65.0 degrees celsius

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.5 amperes resistive load first voltage 1.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+122.00/+221.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

176.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage 28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0