

View Online at <https://aerobasegroup.com/nsn/5930-01-351-0511>

Overall Length:

Between 1.140 inches and 1.260 inches

Overall Height:

Between 0.635 inches and 0.690 inches

Body Diameter:

0.640 inches

Body Height:

Between 0.375 inches and 0.460 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

180.00 actuation point degrees fahrenheit and 160.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Test Data Document:

81349-mil-prf-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-24236/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0

Mil-std (military Standard):

Mil-prf-24236 spec.