

View Online at <https://aerobasegroup.com/nsn/5930-01-351-4752>

Thread Class:

2a

Body Style:

Bushing mount

Body Diameter:

1.000 inches

Bushing Length:

0.540 inches

Body Length:

2.000 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.090 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing w/panel seal

Features Provided:

Actuator seal and holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac and 20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0