

View Online at <https://aerobasegroup.com/nsn/5930-01-351-4754>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture resistant and shock resistant and splashproof and vibration resistant

Overall Length:

2.844 inches

Overall Diameter:

0.844 inches

Case Material:

Metal

Actuator Style:

Round, flush

Actuator Diameter:

0.844 inches

Actuator Height:

0.469 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal and full display lens and mounting hardware and rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.500 amperes inductive dc and 0.500 amperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 0.800 amperes lamp ac

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0