

View Online at <https://aerobasegroup.com/nsn/5930-01-351-7180>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Dustproof and shock resistant and vibration resistant

Overall Length:

1.375 inches

Body Diameter:

0.562 inches

Body Length:

1.281 inches

Overall Diameter:

0.875 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.355 inches and 0.395 inches

Actuator Height:

Between 0.235 inches and 0.265 inches

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

End Application:

1055-01-226-6338 launcher, mine clear

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action, with contact on arm single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

96906-ms25089 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A053a0

Mil-std (military Standard):

Mil-s-8805 spec.