

View Online at <https://aerobasegroup.com/nsn/5930-01-351-7180>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Dustproof and shock resistant and vibration resistant

**Overall Length:**

1.375 inches

**Body Diameter:**

0.562 inches

**Body Length:**

1.281 inches

**Overall Diameter:**

0.875 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.355 inches and 0.395 inches

**Actuator Height:**

Between 0.235 inches and 0.265 inches

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**End Application:**

1055-01-226-6338 launcher, mine clear

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action, with contact on arm single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

96906-ms25089 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A053a0

**Mil-std (military Standard):**

Mil-s-8805 spec.