NSN 5930-01-352-3442

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-352-3442

| Body Style: |
|---|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Oiltight |
| Overall Length: |
| 2.063 inches |
| Overall Height: |
| 3.312 inches |
| Overall Width: |
| 1.750 inches |
| Body Length: |
| 1.875 inches |
| Body Width: |
| 1.400 inches |
| Body Height: |
| 1.719 inches |
| Case Material: |
| Plastic |
| Actuator Length: |
| 1.469 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.781 inches |
| Actuator Width: |
| 1.469 inches |
| Actuator Color: |
| Black single actuator and black single actuator |
| Actuator Inscription: |
| Stop/start single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 dc and 600.0 ac |
| End Application: |
| 4920-01-219-1499 test station, fuel control system components |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Horizontal split lens |
| Nonpile-up Contact Arrangement: |

1 pole, single throw, normally open, double make, momentary action 1st switch unit1 pole, single throw, normally closed, double break, momentary action 2nd switch unit

NSN 5930-01-352-3442

Push Switch - Page 2 of 2



| | Contact Load | Current Rat | ing At Ma | ximum Rat | ed Voltage: |
|--|--------------|--------------------|-----------|-----------|-------------|
|--|--------------|--------------------|-----------|-----------|-------------|

550.0 milliamperes resistive dc and 1.200 amperes resistive dc

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0